



Product Service

# CERTIFICATE

No. Z2 116394 0004 Rev. 01

**Holder of Certificate:** **Guangdong Lesso Banhao  
New Energy Technology Group Co., Ltd.**  
No. 01, Building 9, Lane 3, East of Dengdong Road,  
Longjiang Community, Longjiang Town,  
Shunde District,  
528318 Foshan City, Guangdong Province  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**[Mono Crystalline Silicon Photovoltaic (PV) Module(s)]**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64290223104102

**Valid until:** 2027-11-01

**Date,** 2022-11-02

( Symbol Zhao )



# CERTIFICATE

No. Z2 116394 0004 Rev. 01

## Model(s):

520D(HPM)72(182), 525D(HPM)72(182), 530D(HPM)72(182),  
 535D(HPM)72(182), 540D(HPM)72(182), 545D(HPM)72(182),  
 550D(HPM)72(182);  
 480D(HPM)66(182), 485D(HPM)66(182), 490D(HPM)66(182),  
 495D(HPM)66(182), 500D(HPM)66(182), 505D(HPM)66(182);  
 435D(HPM)60(182), 440D(HPM)60(182), 445D(HPM)60(182),  
 450D(HPM)60(182), 455D(HPM)60(182), 460D(HPM)60(182);  
 390D(HPM)54(182), 395D(HPM)54(182), 400D(HPM)54(182),  
 405D(HPM)54(182), 410D(HPM)54(182), 415D(HPM)54(182);  
  
 640D(HPM)66(210), 645D(HPM)66(210), 650D(HPM)66(210),  
 655D(HPM)66(210), 660D(HPM)66(210), 665D(HPM)66(210),  
 670D(HPM)66(210);  
 580D(HPM)60(210), 585D(HPM)60(210), 590D(HPM)60(210),  
 595D(HPM)60(210), 520D(HPM)54(210), 525D(HPM)54(210),  
 530D(HPM)54(210), 535D(HPM)54(210), 540D(HPM)54(210),  
 545D(HPM)54(210).

## Parameters:

Safety class:	Class II
Max. system voltage:	1500 V d.c.
Fire safety class:	Class C according to UL 790
Construction:	Framed, with Junction box, Cable and Connectors

## Tested according to:

IEC 61215-1:2016  
 EN 61215-1:2016  
 IEC 61215-1-1:2016  
 EN 61215-1-1:2016  
 IEC 61215-2:2016  
 EN 61215-2:2017  
 IEC 61730-1:2016  
 EN IEC 61730-1:2018  
 IEC 61730-2:2016  
 EN IEC 61730-2:2018